



## GLAS-TECH II Filter Cartridges

- liquid filters
- glass microfibre

GLAS-TECH II filter cartridges offer an economical prefiltration solution for both liquids and gases. Providing excellent flow rates and long service life with an exceptional ability to retain both deformable and non-deformable particles.

GLAS-TECH II is made using components of construction that provide optimal results in a wide variety of prefiltration applications. GLAS-TECH II cartridge is a nominally-rated borosilicate microfibre depth matrix that has an exceptionally high dirt-holding capacity. The natural, positive charge of the glass fibre also aids in the retention of negatively charged particulates such as colloidal materials.


Thermal bonding helps to ensure stability through multiple steam cycles. The pleat geometry for each micron rating has been individually optimised to ensure stability through long service life and maximum dirt-loading in the most stringent of processing conditions

### Features and Benefits


- High flow rate reduces processing time
- Long service life minimises change-out frequency
- Thermally resistant for use under aggressive conditions
- Natural positive charge enhances particle retention



### Performance Characteristics



10" Size (250 mm) Cartridge



5" Size (130 mm) Cartridge

## Specifications

### Materials of Construction

■ Filtration Media	: Glass Microfibre
■ Media Binder	: Acrylic
■ Support Layers	: Polyester
■ Structure	: Polypropylene
■ Standard O-rings	: Buna N EPDM Silicone Viton

### Maximum Operating Conditions

71°C (160°F)

### Recommended Operating Conditions

Up to 70 °C (158 °F) continuous operating temperature and higher short-term temperatures during CIP to the following limits:

Temperature		Max. Forward dP	
°C	°F	(bar)	(psi)
24	75	5.5	80
80	176	2.1	30

### Cleaning and Sterilisation

Cartridges with encapsulated inserts may be steam sterilised for multiple cycles at 130°C (266°F) or sanitised for a least ten 30 minute cycles using 80°C (176°F) water. They are also compatible with most other sanitising agents.

For detailed operations procedures and advice on cleaning and sterilisation, please contact the Technical Support Group through your usual domnick hunter contact.

### Applications

- Cutting oils
- Cosmetics
- High viscosity solutions
- General filtration

## Ordering Information

### Cartridges

28	□	9	□	□	-	□	-	□	□
Code   Insert Style	Code   End Fitting	Code   Length (Nominal)	Code   Micron	Code   Seal	Code   Gasket Thickness				
1 None (std) 5 Encapsulated 316L Stainless Steel 6 Encapsulated Polysulphone A* Short Neck	0 DOE 1 DOE 2 Flat / 226 3 Flat / 222 6 Flat / 020 / Internal 7 Fin / 226 8 Fin / 222 G 120 / Internal / Recessed Endcap H 213 Recessed Endcap R 222 / Recessed Blank	05 5" (130 mm) 10 10" (250 mm) 20 20" (500 mm) 30 30" (750 mm) 40 40" (1000 mm)	002 0.25 050 0.5 010 1.0 030 3.0 050 5.0	0 Buna N 1 EPDM 2 Silicone 4 Viton** 5* FEP Viton 6* FEP Silicone N None	1 5mm (0.200") 2 3mm (0.125") 4 (1) 5mm (0.200") and (1) 3mm (0.125") N No Gaskets				

\*code 3 and 8 only

\*o-rings only

\*\*Viton is a registered trademark of E.I. DuPont de Nemours & Co., Inc


Parker domnick hunter has a continuous policy of product development and although the Company reserves the right to change specifications, it attempts to keep customers informed of any alterations. This publication is for general information only and customers are requested to contact our Process Filtration Sales Department for detailed information and advice on a products suitability for specific applications. All products are sold subject to the company's Standard conditions of sale.

PROSEP FILTER SYSTEMS LTD  
Unit G19  
River Bank Way  
Lowfields Business Park  
Elland  
West Yorkshire  
HX5 9DN

**Tel: 01422 377367**  
Fax: 01422 377369

Email: [enquiries@prosep.co.uk](mailto:enquiries@prosep.co.uk)  
[www.prosep.co.uk](http://www.prosep.co.uk)

**Map and Directions to Prosep Filters Limited**



Leave M62 at Junction 24.  
At roundabout adjacent to Cedar Court Hotel take 2nd exit onto dual carriageway (A629), signposted Halifax.  
Take 1st exit slip road.  
At roundabout at end of sliproad, take 3rd exit off.  
This is the entrance to Lowfields Business Park.  
Proceed straight over 1st roundabout.  
At next roundabout take 2nd exit onto River Bank Way - Prosep Filters can be found on the left after the S-bend.

[Link to Google Maps](#)