

Fulflo® Flo-Pac®+ 300, 600 and 700 Series Filter Cartridges

■ Phenolic Resin Bonded
Cellulosic Media

Pleated Series

Special Construction for Organic Solvent Filtration

Parker Fulflo® Flo-Pac®+ Cartridges are the filters of choice for many industrial filtration requirements. Flo-Pac+ Pleated Cartridges are manufactured with premium grade, phenolic impregnated cellulosic filter media for long service life, high flow rate and low pressure drop. Unique epoxy resin bonding of end caps, pleat side seal and gaskets provides excellent resistance to most organic solvents.

Flo-Pac+ Pleated Cartridges are available in 0.5µm, 1µm, 5µm, 10µm, 20µm and 30µm pore sizes (95% removal; β = 20).

Applications

- Alcohols
(methanol, ethanol, butanol)
- Aromatic Hydrocarbons
(toluene, xylene, benzene)
- Aliphatic Hydrocarbons
(hexane, pentane, naphtha)
- Ketones
(acetone, isophorone,
methyl ethyl ketone)
- Halogenated Hydrocarbons
(methylene chloride, chloroform,
perchloroethylene)
- Ethers
(THF, dioxane)
- Glycols
(EG, PEG, DEG)
- Amines
(DEA, TEA, DMEA)
- Esters
(ethyl acetate, cellosolve acetate)



Features and Benefits

- Epoxy bonding of end caps, pleat side seal and gaskets provides resistance to most organic solvents.
- Premium pleated cellulosic media allow high flow capacity at low pressure drop.
- Available in a variety of sizes and configurations to fit most industrial housings.
- Impregnated phenolic resin provides strength, integrity and high contaminant capacity.
- Suitable for operating temperatures to 250°F (121°C).
- Perforated outer metal sleeve protects the media against damage.
- ETP (Electro-tin-plated) steel metal components for aqueous and oil-based applications.
- Gaskets provide positive seals and are available in Viton,* cork and standard vellumoid.
- Recommended range is pH 4-10. Please call for specific recommendation.

Process Filtration Division

PROSEP FILTER SYSTEMS LTD
Unit G19
River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN

Tel: 01422 377367

Fax: 01422 377369

Email: enquiries@prosep.co.uk

www.prosep.co.uk

Map and Directions to Prosep Filters Limited



Leave M62 at Junction 24.

At roundabout adjacent to Cedar Court Hotel take 2nd exit onto dual carriageway (A629), signposted Halifax.

Take 1st exit slip road.

At roundabout at end of sliproad, take 3rd exit off.

This is the entrance to Lowfields Business Park.

Proceed straight over 1st roundabout.

At next roundabout take 2nd exit onto River Bank Way - Prosep Filters can be found on the left after the S-bend.

[Link to Google Maps](#)