



Fulflo® Flo-Pac® 300, 500, 600 and 700 Series Filter Cartridges

■ Phenolic Resin Bonded
Cellulosic Media

Pleated Series

Superior Industrial Filtration From a Pleated Cartridge Design

Parker Fulflo® Flo-Pac® Cartridges are the perfect choice for many industrial filtration requirements. Flo-Pac pleated cartridges contain premium grade, phenolic impregnated cellulosic filter media. Parker's line of pleated cartridges is designed for critical filtration applications, providing long service life, high flow rate and low pressure drop.

Flo-Pac Pleated Cartridges are available in 0.5µm, 1µm, 5µm, 10µm, 20µm and 30µm pore sizes (95% removal; β = 20).

Applications

- Jet Fuels
- Coolants
- Quench Oils
- Refineries
- Solvents
- Lubricating Oils
- Hydraulic Oils
- EDM Dielectrics
- Rolling Mill Oils
- Processing Liquids



Features and Benefits

- Pleated cellulosic media allow high flow capacity at low pressure drop.
- Available in a variety of sizes and configurations to fit most industrial housings.
- Phenolic resin impregnated to provide strength, integrity and high contaminant capacity.
- Suitable for operating temperatures to 250°F (121°C).
- Outer sleeve protects the media from damage.
- ETP (Electro-tin-plated) steel metal components for both aqueous and oil-based applications.
- Buna-N gaskets are standard. Other materials are available.

Process Filtration Division

