PHF Demi Filter Housing

Industrial air / liquid



- Industrial demi element air / liquid housings
- Available in 5"with Demi Z style locator
- Range of closure options



Specifications

Materials of Construction

Housing: 316L/1.4404

Surface Finish

Internal Upstream: Mechanical polishing

Internal Downstream: BSP: Mechanical polishing to <0.8µm Ra

Triclamp: Mechanical polishing to <0.4µm Ra

External: Mechanical polishing

Cartridge Socket: Z style Number of Cartridges: 1

Technical Design Data

Design Code: PED 2014/68/EU
PED Category: SEP (Art 4.3)
PED Fluid Group: 1 or 2


PED Fluid State: Gas or Liquid


ATEX Regulation: Group 2, CAT 2 Gas & Dust Fluid GR IIC, Zone 1 & 21


Design Pressure: -1 to 10 bar at 150°C

Certification: Supplied as standard with IOMI and vessel inspection certificate

Dimensions









Height Dimensions		
BSP Closure S (2)	L=198	R=41
BSP Closure S, (3)	L=198	R=41
Clamp Closure S (2)	L=198	R=41
Clamp Closure S [3]	I =216	D-50

Ordering Information





^{**} Closure system C and B for PED Group 2, H for PED Group 1

Vent and drain plugs/blanks not supplied as standard, available as separate parts.









WE ARE YOUR 'ONE STOP SHOP' FOR ALL OF YOUR FILTRATION REQUIREMENTS

LIQUID FILTRATION

- CARTRIDGES
- FILTER BAGS
- VESSELS
- STRAINERS

AIR FILTRATION

- VENT FILTERS
- STERILE AIR
- VACCUM
- AIR-CONDITIONING
- FILTER MEDIA

DOMESTIC

- ULTRAVIOLET
- TREATMENT OF BOREHOLES, SPRINGS & WELLS
- WATER TESTING

FUEL FILTRATION

• DIESEL, AVIATION



Prosep Filter Systems Ltd Unit G19, River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN Phone: 01422 377367 email: sales@prosep.co.uk www.prosep.co.uk





