

PRODUCT INFORMATION

PROSEP
FILTER SYSTEMS LTD

FILTER MEDIA GRADE DSR2/220 (15/150)

The filter media is manufactured from non toxic thermally bonded fibre which is built up progressively to form a high density matrix with superb mechanical strength.

Application

Particularly suitable for all air conditioning systems, high velocity induction units and as a pre-filter for high efficiency secondary filters.

TECHNICAL DATA

AVERAGE ARRESTANCE	%	84
RATED AIR FLOW	M3/H/M2	5400
INITIAL AIR VELOCITY	M/S	1.5
INITIAL RESISTANCE	Pa	15
FINAL RECOMMENDED RESISTANCE	Pa	160
TEMPERATURE RESISTANCE	Deg C	100
MAXIMUM OPERATING HUMIDITY	% rh	100
FILTER DEPTH	MM	12mm
WASHABILITY		Semi regenerable
FILTER CLASSIFICATION	G3 BS 6540/PART 1	

FLAME RESISTANCE

BS 5588/CP413 NON COMBUSTIBLE

SPECIAL FEATURES

THERMALLY BONDED
FREE OF ALL TOXIC
FUME EMISSIONS

SUPPLY OPTIONS

ROLL LENGTH	Meters	20
ROLL WIDTH	Meters	2.0
SPECIAL DIMENSIONS AND PADS		TO CUSTOMER'S REQUIREMENTS

Prosep Filter Systems Ltd
Unit G19, River Bank Way,
Lowfields Business Park,
Elland, West Yorkshire
HX5 9DN

Phone: 01422 377367
email: sales@prosep.co.uk
www.prosep.co.uk



for all your filter requirements