

## PRODUCT INFORMATION

### MEDIA GRADE DSR4/220 290W

#### Description

The filter media is manufactured from non toxic thermally bonded fibre which is built up progressively to form a high density matrix with superb mechanical strength.

#### Application

Particularly suitable for all air conditioning installations as a pre-filter to more efficient secondary filters and may be used as a pre-filter in paint spray booths.

#### TECHNICAL DATA

AVERAGE ARRESTANCE	%	92
RATED AIR FLOW	M3/H/M2	5400
INITIAL AIR VELOCITY	M/S	1.5
INITIAL RESISTANCE	Pa	25
FINAL RECOMMENDED RESISTANCE	Pa	210
TEMPERATURE RESISTANCE	Deg C	100
MAXIMUM OPERATING HUMIDITY	% rh	100
FILTER DEPTH	mm	25
WASHABILITY	SEMI-REGENERABLE	
FILTER CLASSIFICATION	G4	
	BS 6540/PART 1	

#### FLAME RESISTANCE

BS 5588/CP413 NON COMBUSTIBLE

#### SPECIAL FEATURES

THERMALLY BONDED  
FREE OF ALL TOXIC  
FUME EMISSIONS

#### SUPPLY OPTIONS

ROLL LENGTH	Meters	20
ROLL WIDTH	Meters	2.0

SPECIAL DIMENSIONS AND PADS TO CUSTOMER'S REQUIREMENTS

**Prosep Filter Systems Ltd**  
Unit G19, River Bank Way,  
Lowfields Business Park,  
Elland, West Yorkshire  
HX5 9DN

**Phone: 01422 377367**  
email: [sales@prosep.co.uk](mailto:sales@prosep.co.uk)  
[www.prosep.co.uk](http://www.prosep.co.uk)



*for all your filter requirements*