

700 Series

# 700 Series Overview



	745R30	760R30	790R30	790R3024	7125R30	7125R3024
<b>Power</b>	12 volt	12 volt	12 volt	24 volt	12 volt	24 volt
<b>Max Flow Rate</b>	45 GPH (170 LPH)	60 GPH (227 LPH)	90 GPH (341 LPH)	90 GPH (341 LPH)	120 GPH (454 LPH)	120 GPH (454 LPH)
<b>Port Size (SAE J1926)</b>	7/8"-14 UNF	7/8"-14 UNF	7/8"-14 UNF	7/8"-14 UNF	7/8"-14 UNF	7/8"-14 UNF
<b>Height</b>	10.8 in. (25.7 cm)	11.8 in. (28.4 cm)	12.8 in. (31.2 cm)	12.8 in. (31.2 cm)	15.2 in. (38.5 cm)	15.2 in. (38.5 cm)
<b>Width</b>	4.3 in. (11.0 cm)	4.3 in. (11.0 cm)	4.3 in. (11.0 cm)	4.3 in. (11.0 cm)	4.3 in. (11.0 cm)	4.3 in. (11.0 cm)
<b>Depth</b>	6.5 in. (16.5 cm)	6.5 in. (16.5 cm)	6.5 in. (16.5 cm)	7.1 in. (18.0 cm)	6.5 in. (16.5 cm)	7.1 in. (18.0 cm)
<b>Weight (dry)</b>	4.5 lb (2.0 kg)	5.5 lb (2.5 kg)	6.5 lb (3.0 kg)	6.5 lb (3.0 kg)	6.7 lb (3.03 kg)	6.7 lb (3.03 kg)
<b>Clean Pressure Drop</b>	0.7 PSI (4.8 kPa)	0.7 PSI (4.8 kPa)	0.7 PSI (4.8 kPa)	0.7 PSI (4.8 kPa)	0.7 PSI (4.8 kPa)	0.7 PSI (4.8 kPa)
<b>Ambient Temp. Range</b>	-40° to +250°F (-40° to +121°C)					
<b>Max. Fuel Temp.</b>	190°F (32°C)					

**Note:** All Racor filter materials and seals are compatible with ultra-low sulphur diesel (ULSD) fuel and B2 to B20 Biodiesel.



01422 377367



enquiries@prosep.co.uk

**PROSEP**  
FILTER SYSTEMS LTD

WE ARE YOUR **'ONE STOP SHOP'** FOR ALL  
OF YOUR FILTRATION REQUIREMENTS

**LIQUID FILTRATION**

- CARTRIDGES
- FILTER BAGS
- VESSELS
- STRAINERS

**AIR FILTRATION**

- VENT FILTERS
- STERILE AIR
- VACCUM
- AIR-CONDITIONING
- FILTER MEDIA

**DOMESTIC**

- ULTRAVIOLET
- TREATMENT OF BOREHOLES,  
SPRINGS & WELLS
- WATER TESTING

**FUEL FILTRATION**

- DIESEL, AVIATION



**Prosep Filter Systems Ltd**  
Unit G19, River Bank Way,  
Lowfields Business Park,  
Elland, West Yorkshire  
HX5 9DN

**Phone: 01422 377367**  
email: [sales@prosep.co.uk](mailto:sales@prosep.co.uk)  
[www.prosep.co.uk](http://www.prosep.co.uk)



*for all your filter requirements*