

Fulflo® DuraBond™ Cartridges

Economical Filtration with High-Strength,
Thermally-Bonded Depth Cartridges

Parker's Fulflo® DuraBond™ cartridges are the most economical high strength filter cartridges available. Featuring an integral rigid thermally bonded construction, the DuraBond provides consistent filtration for a wide variety of fluids. Its fixed pore structure acts as a sieve-like particle "classification" filter for pigmented coatings allowing pigments to pass while stopping large agglomerates.

DuraBond cartridges are available in nominal ratings of 1µm, 3µm, 5µm, 10µm, 25µm, 50µm, 75µm and 100µm.



Contact Information

Parker-Hannifin Corporation
domnick hunter
Process Filtration - North America
2340 Eastman Avenue
Oxnard, California, USA 93030

toll free +1 877 784 2234
phone +1 805 604 3400
fax +1 805 604 3401
dhpsales.na@parker.com

www.parker.com/processfiltration

Benefits

- Fixed pore structure provides efficiency, integrity and optimum particle retention
- Thermally bonded bi-component fiber matrix provides rigid dimensionally stable construction without fiber migration
- Rigid construction eliminates contaminant unloading and channeling
- Corrugated porous surface maximizes dirt holding capacity
- Silicone free construction will not change coating properties
- FDA grade polypropylene (DOE only) certified to ANSI/NSF61 standard for contact with drinking water components
- Polyolefin construction provides broad chemical compatibility for a variety of applications
- All materials of construction are FDA listed as acceptable for potable and edible liquid contact according to CFR Title 21
- Easily disposed by shredding, incinerating or crushing
- Construction provides particle "classification" effect with pigmented coatings
- Double-open-end style is self-sealing without separate gasket material

Applications

- Photographic Chemicals
- DI Water
- Plating Solutions
- Bleach
- RO Pre-filtration
- Organic Solvents
- Oil Field Fluids
- Membrane Pre-filtration
- Industrial Coatings
- Magnetic Coatings
- Potable Water
- Process Fluids



ENGINEERING YOUR SUCCESS.

Fulflo® DuraBond™ Cartridges

Specifications

Materials of Construction:

- Filter Medium:
Thermal Bonded bi-component matrix of polypropylene/ polyethylene
- End Caps/Adapters (optional):
Polyolefin copolymer
- Seal Options:
Various; refer to Ordering Information

Dimensions:

1-¹/₁₆ in (27mm) ID x 2-⁷/₁₆ (62mm) in OD
10, 20, 30, 40, and 50 in. continuous nominal lengths

Maximum Recommended Operating Conditions:

- Temperature: 175°F (80°C)
- Pressure:
- 100psid (6.8bar)@72°F (27°C)
- 50psid (3.4bar)@175°F (80°C)
- Flow rate:
5gpm (18.9 lpm) per 10 in. length
- Change-out ΔP: 30psi (2.1bar)

Nominal Filtration Ratings

(90% efficiency):
1, 3, 5, 10, 25, 50, 75, 100 μm

DBC Flow Factors

Rating (μm)	Aqueous Service psi/gpm per 10 in cartridge
DBC1	0.109
DBC3	0.087
DBC5	0.073
DBC10	0.058
DBC25	0.031
DBC50	0.022
DBC75	0.015
DBC100	0.012

DBC Length Factors

Length (in)	Length Factor
9.75	1.0
10.00	1.0
19.50	2.0
20.00	2.0
29.25	3.0
30.00	3.0
39.00	4.0
40.00	4.0
50.00	5.0

Flow Rate and Pressure Drop Formulas

Flow Rate (gpm):

Clean $\Delta P \times \text{Length Factor}$
Viscosity \times Flow Factor

Clean ΔP :

$\text{Flow Rate} \times \text{Viscosity} \times \text{Flow Factor}$
Length Factor

1. Clean ΔP ispsi differential at start.
2. Viscosity is centistokes. Use Conversion Tables for other units.
3. Flow Factor is $\Delta P/\text{GPM}$ at 1cks for 10 in. (or single).
4. Length Factors convert flow or ΔP from 10 in. (single length) to required cartridge length.

Liquid Particle Retention Ratings (μm) @ Removal Efficiency of:

Cartridge	β=1000 99.9%	β=100 99%	β=20 95%	β=10 90%
DBC1	5	4	2	1
DBC3	10	8	4	3
DBC5	20	16	10	5
DBC10	30	25	15	10
DBC25	55	50	30	25
DBC50	90	80	70	50
DBC75	>100	>100	100	75
DBC100	>100	>100	>100	100

Beta Ratio (β) = $\frac{\text{Upstream Particle Count @ Specified Particle Size and Larger}}{\text{Downstream Particle Count @ Specified Particle Size and Larger}}$

Percent Removal Efficiency = $\left(\frac{\beta-1}{\beta}\right) \times 100$

Performance determined per ASTM F-795-88, Single-Pass Test using AC test dust in water at a flow rate of 2.5gpm per 10 in (9.5 lpm per 254 mm).

Ordering Information

Cartridge Code		Micron Rating	Nominal Length			End Cap Configuration		Seal Material	
DBC	DuraBond	(μm)	CODE	IN.	mm	CODE	DESCRIPTION	CODE	MATERIAL
		1	9-4	9- ³ / ₄	248	None	Double Open End (DOE) w/o gaskets	None	No Seal Mat. (Std. DOE)
		3	10	10	254	AR	020 Flat (Gelman)	A	Poly foam gaskets w/collars (DO only)
		5	19-4	19- ¹ / ₂	495	DO	DOE	E	EPR
		10	20	20	508	LL	120 O-ring both ends**	N	Buna-N
		25	29-4	29- ¹ / ₄	743	LR	120 O-ring/Recessed**	S	Silicone (O-ring only)
		50	30	30	762	OB	Std. open end/Polypropylene spring closed end	T	PFA Encapsulated Viton® (222, 226 O-ring only)
		75	39-4	39	991	PR	213 O-ring/Recessed**	V	Viton®
		100	40	40	1016	SC	226 O-ring/Flat	W	Poly foam gaskets w/o collars (DO only)
			50	50	1270	SF	226 O-ring/Fin		
						TC	222 O-ring/Flat		
						TF	222 O-ring/Fin		
						TX	222 O-ring/Flex fin		
						XA	DOE w/extended core		
						XB	Ext. core open end polypropylene spring closed end		

**Available only in 9-³/₄" (9-4) and 19-¹/₂" (19-4) lengths.

Specifications are subject to change without notification.
For User Responsibility Statement, see www.parker.com/safety



© 2010 Parker-Hannifin Corporation
domnick hunter Process Filtration - North America
All Rights Reserved
Viton is a registered trademark of E.I. DuPont de Nemours & Co., Inc.

DS_IP_DuraBond Rev. A



01422 377367



enquiries@prosep.co.uk

PROSEP
FILTER SYSTEMS LTD

WE ARE YOUR **'ONE STOP SHOP'** FOR ALL
OF YOUR FILTRATION REQUIREMENTS

LIQUID FILTRATION

- CARTRIDGES
- FILTER BAGS
- VESSELS
- STRAINERS

AIR FILTRATION

- VENT FILTERS
- STERILE AIR
- VACCUM
- AIR-CONDITIONING
- FILTER MEDIA

DOMESTIC

- ULTRAVIOLET
- TREATMENT OF BOREHOLES,
SPRINGS & WELLS
- WATER TESTING

FUEL FILTRATION

- DIESEL, AVIATION



Prosep Filter Systems Ltd
Unit G19, River Bank Way,
Lowfields Business Park,
Elland, West Yorkshire
HX5 9DN

Phone: 01422 377367
email: sales@prosep.co.uk
www.prosep.co.uk



for all your filter requirements