

PLEATED POLYESTER CARTRIDGES



Features and Benefits

- Washable filter cartridge
- High efficiency up to 90%
- 5, 20 30 and 50 micron options available
- Components approved by FDA, NSF and PZH
- Working temperature: 2 - 52°C
- Integral gasket
- Cost effective filtration

These pleated polyester filter cartridges are manufactured from a fibrous polyester which increases the depth of filter media giving greater dirt holding capacity and increasing service life. The pleat pack ends are fully immersed in a vinyl plastisol end cap which incorporates the sealing gasket and ensures complete integrity of the pleat pack. The high dirt holding capacity and efficiency of this range means that these filters are particularly useful for prefiltration before Ultra violet treatment and in other private water supply duties where long service life is essential.

Model 'PLPO'	Height	Diameter	Filtration	Flow Rate	Pressure Drop
	Inch	Inch	Micron	L/Min	Bar
	9 7/8	2 1/2	10, 30, 50	20	0.2 - 0.4
	20	2 1/2	5, 20, 30, 50	20	0.2 - 0.4
	9 7/8	4 1/4	5, 20, 30, 50	30	0.2 - 0.4
	20	4 1/4	5, 20, 30, 50	60	0.2 - 0.4

Prosep Filter Systems Ltd
Unit G19, River Bank Way,
Lowfields Business Park,
Elland, West Yorkshire
HX5 9DN

Phone: 01422 377367
email: sales@prosep.co.uk
www.prosep.co.uk



for all your filter requirements